

# Odor Guard® Manhole Inserts

Sewer Odor Protection that is  
“Built Tough to Last Long”



Standard Odor Guard®



Odor Guard® - MD



Odor Guard® - LD

Recommended Use	Odor Guard	Odor Guard - MD	Odor Guard - LD
Media Capacity	3 cubic foot	1 ½ cubic foot	¾ cubic foot
Use for Wetwell	Recommended	Not Recommended	Not Recommended
Vent Relief Valve Vaults	Recommended	Light Duty	Not Recommended
Receiving Manhole	Recommended	Moderate Duty	Not Recommended
Gravity Manhole	Recommended	Moderate Duty	Light Duty

Technical Specification	Odor Guard Standard	Odor Guard - MD	Odor Guard - LD
Media Capacity	3 cubic foot	1 ½ cubic foot	¾ cubic foot
H2S Uptake Capacity	30 pounds	15 pounds	7.5 pounds
Insert Depth Required	30 inches	18 inches	14 inches
Weight Empty/Final	50/135 lbs	15/55 lbs	15/40 lbs
Market Equivalent	Largest Insert on the Market	Oxidizer Inserts	Carbon Inserts
Materials of Construction	Stainless Steel & PVC	Stainless Steel & Plastic	Stainless Steel & Plastic
Air Flow In & Out	Radial	Vertical	Vertical
Inflow Protection	Available	Standard	Standard
Initial Cost* Single Unit	\$1,650	\$895	\$550
Media Replacement**	\$340	\$175	\$99

\* For Odor Guard Units to fit under lid diameters up to 25 inches. For units larger than 25 inches add \$100.00 per unit. Multiple order discounts are available. Odor Guard non-hazardous odor control media is included with the purchase of the Odor Guard units to create a highly effective and long-lasting system to treat odor problems. Prices quoted are with all components, media, and complete for immediate installation. Replacement media for Odor Guard-MD and Odor Guard-LD units comes in convenient Filter-Pail cartridges for quick and easy changeouts.

\*\*High-capacity non-hazardous Odor Control Media is 99% natural and recycled materials to help protect our environment while giving you the performance you need. The system effortlessly breaths treated exhaust gas out and allows air in. The special media is a mix of solid organic and inorganic odor reactants and counteractants. Hydrogen sulfide and light mercaptans are safely and irreversibly reacted away while attacking other odors present. The media thrives on the wet humid environment encountered in manholes and is not adversely affected by occasional wetting. This unique high-capacity, lightweight and very low-pressure drop media was specially developed for sewer-type odor control.

Sierra Environmental Technologies, LLC.

18545 Bridlegate Lane, Wildwood, MO. 63069

Tel: 636-273-5189

Fax: 636-273 – 4509

Email: dnokes@prodigy.net

**AMERICAN MADE WITH PRIDE!**