



Sierra Environmental Technologies, LLC

SWEET-AIRE GC 60

A granular activated carbon manufactured from high quality lignite coal specifically for odor control applications.

The virgin activated carbon achieves its high H₂S capacity due to its naturally inherent composition and the optimized activation that maximizes the desired porosity of the activated carbon.

- Designed for vapor phase treatment
- Highly developed pore structure
- Highest hydrogen sulfide capacity
- Low pressure drop characteristics

TYPICAL PROPERTIES

Parameter	Unit	Value	Method
Type		Lignite coal	
Surface area	m ² g ⁻¹	900	BET N ₂
Hydrogen Sulfide Capacity	gm/cc	0.20	ASTM D4607
Hydrogen Sulfide Capacity	gm/gm	0.50	
Moisture, as packed	% (max.)	8	ASTM D2867
Apparent density	gm/mL	0.40	
Bulk Density	lbs/cu.ft	25	
Mean Particle Diameter	mm	3.4	
Mesh size (U.S. sieve series):			
Greater than 4 mesh, 4.75 mm	% (max.)	10	
Less than 8 mesh, 2.36 mm	% (max.)	5	

Packaging: 40 lbs. Polypropylene bags and 1000 lbs. Super Sacks

For General Information Only, not to be used as purchasing specifications

This information is offered solely for your consideration and verification. It has been gathered from reference materials and / or test procedures and is believed to be true and accurate. None of this information shall constitute a warranty or representation, expressed or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes.

8.29.08